



**Adhesive  
Solutions**

GROUP OF COMPANY

R/O- Plot No. 120, A Block First Floor, Qutub Vihar Phase-1, Near Sec-19, Dwarka, New Delhi-110071  
M- +91 9871417131, +91 8376920360, E-admin@adhesivesolutions.in,  
Web- www.adhesivesolutions.in

## Tartan™ Brand No. 200 Masking Tape

**DESCRIPTION:** A utility purpose paper tape used for holding, bundling, sealing, non-critical masking and a vast number of other jobs where a pressure-sensitive tape is needed.

### **CONSTRUCTION:**

Backing: Natural colored crepe paper  
Adhesive: Rubber  
Standard Roll Length: 60 Yards (55 meters)

### **TYPICAL PHYSICAL PROPERTIES:**

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

### **ASTM TEST METHOD**

Adhesion to Steel:	32 oz./in. width (35 N/100mm)	D-3330 Tensile
Strength:	20 lbs./in. width (350 N/100mm)	D-3759
(Break)		
Elongation:	8%	D-3759 (Break)
Tape Thickness:	0.0055 in. (.014mm)	D-3652

### **GENERAL INFORMATION:**

1. Tape No. 200 is typically used at room temperature but will function up to 200°F (93°C) for periods up to 1/2 hour.
2. Tape No. 200 should not be subjected to outdoor or UV exposure.
3. Can be qualified to meet Federal Specification PPP-T-42C Type I and commercial Item Description CID-A-A-883A Type I.

### **SHELF LIFE:**

To obtain best performance, use this product within one year from date of manufacture and store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton.

**FEATURES**

**ADVANTAGES**

**BENEFITS**

Rubber adhesive	Instant adhesion	Sticks easy/less labor
	Good holding power	Resists lifting or curling/less rework
Crepe paper backing	Conformability	Maintains integrity when formed around a corner
Backing saturant	Easy tear	Resists slivering yet hand tearable
	Sliver resistance	One piece removal
Backsize treatment	Controlled unwind	Dispenses evenly/less likely to tear off roll/works well on paper dispensers
Manufactured without solvents	Eliminates use of organic solvents during manufacture	Minimizes energy and raw material consumption/reduced environmental stresses

Technical Data: All physical properties, statements, and recommendations are either based on tests we believe to be reliable or our experience, but they are not guaranteed. 3M recommends each user determine the suitability of the masking paper, film or tape for the intended use.

Warranty and Limited Remedy: THE FOLLOWING WARRANTY IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE AND ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, A CUSTOM OR USAGE OF TRADE:

3M warrants its masking papers, films and tapes will be free from all defects in materials and manufacture. If masking paper, film or tape is proved to be defective, then the exclusive remedy and 3M's and seller's sole obligation shall be, at 3M's option, to replace the quantity of the product which is proved to be defective or to refund the purchase price.

Limitation of Liability: 3M and seller shall not be liable for direct, indirect, special, incidental or consequential damages based upon breach of warranty, breach of contract, negligence, strict liability or any other legal theory.

The foregoing Warranty and Limited Remedy and Limitation of Liability may be changed only by a written agreement signed by authorized officers of 3M and seller .